



# Typical Properties Sheet

12/2/2014

Product: ESD FOAM

| <u>Physical Property</u>         | <u>Value</u>                      | <u>Test Method</u> |
|----------------------------------|-----------------------------------|--------------------|
| Color                            | Black                             |                    |
| Density (lbs / ft <sup>3</sup> ) | 1.7 - 1.9                         | ASTM D-3574-01     |
| Indent Force Deflection<br>@ 25% | 45 - 55                           | ASTM D-3574-01     |
| Surface Resistance (Ohms/sq)     | 10 <sup>4</sup> - 10 <sup>9</sup> | ASTM D257          |
| Volume Resistance (Ohms - CM)    | 10 <sup>4</sup> - 10 <sup>9</sup> | ASTM D257          |
| Flame Resistance                 | N/A                               |                    |

This information is based on actual testing in a controlled environment. However, as conditions of use are not within our control, Amcon does not guarantee from use of such products or other information herein; no warranty expressed or implied is given. It is the user's responsibility to determine the appropriateness of the products for their specific end uses.

**WARNING: URETHANE FOAM IS FLAMMABLE!**

**Urethane Foam should not be exposed to open flame or other ignition sources.  
Urethanes burn rapidly with great heat and release gases which are extremely hazardous.**

5360 Main St. NE Minneapolis, MN 55421

Ph. 888-360-8050

**[www.amconfoam.com](http://www.amconfoam.com)**