



# Technical Data Sheet

6/2/2006

Product: **Softshield**

<u>Physical Property</u>	<u>Value</u>	<u>Test Method</u>
Color	Black	
Density (lbs / ft3)	1.7 - 1.9	ASTM D-3574-01
Indent Force Deflection @ 25%	45 - 55	ASTM D-3574-01
Surface Resistance (Ohms/sq)	$10^3 - 10^5$	ASTM D257
Ohms (point to point)	$10^3 - 10^5$	
Volume Resistance (Ohms - CM)	$10^3 - 10^5$	ASTM D257
Static Decay Time (in seconds)	.01 max	
Flame Resistance	N/A	

This information is based on actual testing in a controlled environment. However, as conditions of use are not within our control, Amcon does not guarantee from use of such products or other information herein; no warranty expressed or implied is given. It is the user's responsibility to determine the appropriateness of the products for their specific end uses.

**WARNING: URETHANE FOAM IS FLAMMABLE!**  
**Urethane Foam should not be exposed to open flame or other ignition sources.**  
**Urethanes burn rapidly with great heat and release gases which are extremely hazardous.**

5360 Main St. NE Minneapolis, MN 55421

Ph. 888-360-8050

**[www.amconfoam.com](http://www.amconfoam.com)**