



Typical Properties Sheet

11/8/2018

Product: **4400**

| <u>Physical Property</u> | <u>Value</u> | <u>Test Method</u> |
|----------------------------------|--------------|--------------------|
| Color | Varies | |
| Density (lbs / ft3) | 1.7 - 1.9 | ASTM D-3574-01 |
| Indent Force Deflection @ 25% | 40 - 48 | ASTM D-3574-01 |
| Tensile Strength (psi) | 10 | ASTM D-3574-01 |
| Tear Strength (lbs/lin inch) | 1 | ASTM D-3574-01 |
| Elongation (%) | 100 | ASTM D-3574-01 |

This product has been tested and found to comply with Section 3 of the California Technical Bulletin 117-2013.

This information is based on actual testing in a controlled environment. However, as conditions of use are not within our control, Amcon does not guarantee from use of such products or other information herein; no warranty expressed or implied is given. It is the user's responsibility to determine the appropriateness of the products for their specific end uses.

WARNING: URETHANE FOAM IS FLAMMABLE!

**Urethane Foam should not be exposed to open flame or other ignition sources.
Urethanes burn rapidly with great heat and release gases which are extremely hazardous.**

5360 Main St. NE Minneapolis, MN 55421

Ph. 888-360-8050

www.amconfoam.com